



Castrol Chain Spray

For all makes of motorcycles

Description

Castrol Chain Spray is a high performance motorcycle chain lubricant providing excellent performance under extreme on road and off road riding conditions.

Application

Aerosol can spray application. Suitable for all makes of motorcycles.

Characteristics

- Extends chain life.
- Spray extension for easy application.
- Completely wets chain surfaces.
- Reduces wear.
- Adhesion prevents fling off at low and high speed centrifugal forces.
- High viscosity base oil.
- Highly viscous and non-drip
- Contains extreme pressure and anti wear additives.
- Excellent water resistance.
- Contains soluble - moly for reduced friction and high load.

Typical Characteristics

Name	Method	Units	Typical
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	220
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.25
Viscosity Index	ASTM D2270	None	100
Timken OK Load		kg	220

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Chain Spray

15 Jan 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za