



Vecton 15W-40

Advanced engine oil

Description

Castrol Vecton 15W-40 is an advanced heavy duty diesel engine oil formulated with unique System 5 Technology™ for up to 20% better engine performance

Application

Castrol Vecton 15W-40 is suitable for use in a wide range of US, European and Japanese heavy duty diesel engines in both on and off-road applications including severe applications such as high loads and multi-trailer applications.

Castrol Vecton 15W-40 is suitable for use with biodiesel per OEM recommended drain intervals

Advantages

Modern engines operate in constantly changing conditions which impacts on engine performance. Castrol Vecton 15W-40's unique System 5 Technology™ responds to these changing conditions to maximise engine performance in 5 key areas:

1. Fuel consumption: Fights oil thickening, resulting in better fuel efficiency.
2. Oil consumption: Fights piston deposits, resulting in lower oil consumption.
3. Oil drain interval: Fights contaminants, resulting in longer drain intervals.
4. Component life: Fights wear and corrosion, enhancing the life of critical engine components.
5. Power: Fights soot, improving engine power all the way through the oil drain.

Castrol Vecton 15W-40 with unique System 5 Technology™ adapts to changing engine conditions delivering up to 20% better engine performance*.

* in independent laboratory tests Castrol Vecton 15W-40 performance up to 20% better than API standard limits for oil thickening, piston deposits, soot handling, wear and corrosion

Typical Characteristics

Name	Method	Units	Vecton 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.885
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.4
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	106.4
Viscosity Index	ASTM D2270	None	139
Ash, Sulphated	ASTM D874	% wt	1.36
Total Base Number, TBN	ASTM D4739	mg KOH/g	10.5
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	224

Product Performance Claims

ACEA E5, E7
API CI-4/SL
DHD-1
CAT ECF-2
Cummins CES 20.076, 20.077, 20.078
Mack EO-M Plus, EO-N
MAN M 3275-1
MB-Approval 228.3
RVI RLD-2
Volvo VDS 3

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Vecton 15W-40
17 Feb 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol BP Petco Liability Ltd. Co., Floor 7, Central Plaza Building, 17 Le Duan Avenue, District 1, Ho Chi Minh City, Vietnam
Customer Service: +848 3821 9153
www.castrol.com