



Castrol Magnatec 5W-40 A3/B4

Instant protection from the moment you turn the key

Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oil drains off critical engine parts, however Castrol Magnatec's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection.

Castrol Magnatec's unique formulation protects from the moment you turn the key, dramatically reducing* engine wear. Now with ultra-refined molecules, for protection you can see, hear and feel. Castrol Magnatec. Instant protection from the moment you turn the key.

**As tested in the industry Sequence IVA wear test.*

Application

Castrol Magnatec 5W-40 A3/B4 is suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA A3/B4, A3/B3, API SN/CF or earlier specification 5W-40 lubricant.

Castrol Magnatec 5W-40 A3/B4 is approved for use in vehicles from leading manufacturers, please refer to the specifications section and your vehicle handbook.

Advantages

Castrol Magnatec's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down.
- Cling to your engine forming an extra layer that protects during start up and beyond.
- Bond to metal surfaces to make engine parts more resistant to wear.
- Are combined with synthetic technology to provide increased protection in high and low temperature applications.
- Provide continuous protection for all driving conditions, styles and temperatures.

Castrol Magnatec 5W-40 A3/B4 delivers superior performance under extreme cold start up conditions relative to thicker grades.

Typical Characteristics

Name	Method	Units	Castrol Magnatec 5W-40 A3/B4
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.95
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6270
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	84.61
Viscosity Index	ASTM D2270	None	170
Pour Point	ASTM D5950	°C	-42
Flash Point, PMCC	ASTM D93	°C	211

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
BMW Longlife-01
MB-Approval 226.5/ 229.3
Renault RN 0700 / RN 0710
VW 502 00 / 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Magnatec 5W-40 A3/B4
29 Sep 2014
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za