



Optigear Synthetic X 320 WTO

Synthetic Gear Oil

Description

Castrol Optigear™ Synthetic X 320 WTO is based on synthetic hydrocarbons and a special plastic deformation (PD) and surface improvement additive package. The additive package, when activated by high specific loads and corresponding temperatures, helps to equalize surface roughness without creating abrasion leading to the surface improvement (plastic deformation).

Optigear Synthetic X 320 WTO is a CLP-HC gear oil (according to DIN 51502) and exceeds the minimum requirements according to DIN 51517 (2003), part 3, CLP gear oils.

Application

Optigear Synthetic X 320 WTO may be used in spur gear, bevel gears or planetary gear units and in heavy loaded gear units, e.g. wind turbine main gears. It is also suitable for the lubrication of oil-lubricated rolling bearings.

Depending on the specific application, Optigear Synthetic X may be used in an operating temperature range from -35 °C to +95 °C.

Advantages

- High load carrying capacity.
- Superior micro pitting protection.
- Excellent friction reduction.
- Good filtration properties.
- Excellent bearing lubrication suitability.

Typical Characteristics

Name	Method	Units	Optigear Synthetic X 320 WTO
ISO Viscosity Grade	-	-	320
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	852
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	325
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	40.8
Viscosity Index	ISO 2909 / ASTM D2270	-	179
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	>250/482
Pour Point	ISO 3016 / ASTM D97	°C/°F	-45/-49
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass
Copper corrosion (3 hrs@100°C/212°F)	ISO 2160 / ASTM D130	Rating	1a
FE-8 Bearing Wear test - increased load (F.562831.01-7.5/100-80)	DIN 51819-3 (modified)	roller wear (Mw50)	<10
FE-8 Bearing Fatigue test (F.562831-75/100-70 800 hrs)	DIN 51819-3 (modified)	roller wear (Mw50)	<20
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>14
FZG Micropitting test @ 60°C/140°F	FVA 54-7	Failure Load Stage / Micropitting Rating	>10/High
FZG Micropitting test @ 90°C/194°F	FVA 54-7	Failure Load Stage / Micropitting Rating	>10/High
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	<100/10

Subject to usual manufacturing tolerances.

Additional Information

Optigear Synthetic X gear oil can be applied by an oil can, oil cup reservoir, splash, spray mist or by automatic dispensing equipment and central or circulation systems. It is compatible with mineral oils and esters. This means that traces up to 3% of previous oil in the gear case after draining will not pose any problems. However, the beneficial effects of the special PD additives are reduced when mixed with other gear oils to achieve an optimum Lifetime of your elastomer sealings we recommend the use of Viton (FKM) based materials.

Optigear Synthetic X 320 WTO

23 Jan 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Limited, Industrial Lubricants & Services Rayala Towers , II Tower , V Floor 781-785 , Anna Salai , Chennai – 600 002

Tel: +91 44 42198899 / 823 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-42198885 Email: CustomerService.India@castrol.com
www.castrol.com/industrial